


END CAPS

ASME/ASTM SA/A403-WP304/304L, WP316/316L

ASME B16.9

Cap



Size	Outside Diameter at Bevel (OD)	Length E	Approximate Weight(kg)				
	mm	mm	10S	STD	40S/40	XS	80S/80
1/2"	21.3	25	0.03	0.04	0.04	0.05	0.05
3/4"	26.7	25	0.04	0.05	0.05	0.09	0.09
1 "	33.4	38	0.09	0.11	0.11	0.13	0.13
1 1/4"	42.2	38	0.11	0.14	0.14	0.22	0.22
1 1/2"	48.3	38	0.13	0.17	0.17	0.34	0.34
2"	60.3	38	0.17	0.23	0.23	0.34	0.34
2 1/2"	73.0	38	0.23	0.39	0.39	0.51	0.51
3"	88.9	51	0.37	0.66	0.66	0.84	0.84
3 1/2"	101.6	64	0.46	0.92	0.92	1.10	1.10
4"	114.3	64	0.59	1.17	1.17	1.61	1.61
5"	141.3	76	0.99	1.91	1.91	2.55	2.55
6"	168.3	89	1.39	2.90	2.90	4.24	4.24
8"	219.1	102	2.38	5.19	5.19	7.76	7.76
10"	273.1	127	4.14	9.15	9.15	13.60	16.20
12"	323.9	152	6.39	15.00	19.00	22.00	26.90
14"	355.6	165	7.98	17.00	23.00	27.00	34.70
16"	406.4	178	10.00	23.00	30.00	30.00	43.50
18"	457.2	203	12.80	29.00	39.00	32.00	72.50
20"	508.0	229	18.50	36.00	67.00	49.00	98.50
22"	558.8	254	22.60	42.00	-	51.00	120.00
24"	609.6	267	30.10	52.00	93.00	60.00	150.00
26"	660.4	267	-	-	-	-	-
28"	711.2	267	-	-	-	-	-
30"	762.0	267	-	-	-	-	-
32"	812.8	267	-	-	-	-	-
34"	863.6	267	-	-	-	-	-
36"	914.4	267	-	-	-	-	-
38"	965.2	305	-	-	-	-	-
40"	1016.0	305	-	-	-	-	-
42"	1066.8	305	-	-	-	-	-
44"	1117.8	343	-	-	-	-	-
46"	1168.4	343	-	-	-	-	-
48"	1219.2	343	-	-	-	-	-

General Notes:

- 1) All dimensions are in mm
- 2) Dimension tolerance are as per ASME B16.9