


Tee

ASME/ASTM SA/A403-WP304/304L, WP316/316L

ASME B16.9

Equal Tee



Size	Outside Diameter at Bevel (mm)	Center-to-End(mm)		Approximate Weight(kg)				
	Run	Run (C)	Outlet (M)	10S	STD	40S/40	XS	80S/80
½"	21.3	25.0	25.0	0.10	0.11	0.11	0.16	0.16
¾"	26.7	29.0	29.0	0.15	0.17	0.17	0.21	0.21
1"	33.4	38.0	38.0	0.30	0.35	0.35	0.42	0.42
1 ¼"	42.2	48.0	48.0	0.49	0.61	0.61	0.75	0.75
1 ½"	48.3	57.0	57.0	0.68	0.92	0.92	1.13	1.13
2"	60.3	64.0	64.0	1.01	1.34	1.34	1.69	1.69
2 ½"	73.0	76.0	76.0	1.47	2.37	2.37	2.92	2.92
3"	88.9	86.0	86.0	2.02	3.38	3.38	4.29	4.29
3-1/2"	101.6	95.0	95.0	2.55	4.47	4.47	5.72	5.72
4"	114.3	105.0	105.0	3.18	5.72	5.72	7.45	7.45
5"	141.3	124.0	124.0	4.97	8.99	8.99	12.00	12.00
6"	168.3	143.0	143.0	6.81	13.30	13.30	19.10	19.10
8"	219.1	178.0	178.0	11.77	24.40	24.40	34.70	34.70
10"	273.1	216.0	216.0	19.19	41.40	41.40	43.00	53.60
12"	323.9	254.0	254.0	28.54	46.00	53.60	56.00	69.50
14"	355.6	279.0	279.0	35.66	53.00	61.78	80.80	99.78
16"	406.4	305.0	305.0	44.11	66.70	76.55	100.00	114.23
18"	457.2	343.0	343.0	55.88	83.90	124.32	111.00	150.00
20"	508.0	381.0	381.0	77.32	104.00	164.22	138.00	207.00
22"	558.8	419.0	419.0	93.67	126.00	-	167.00	250.00
24"	609.6	432.0	432.0	115.52	139.00	255.30	185.00	319.00
26"	660.4	495.0	495.0	-	176.00	-	234.00	-
28"	711.2	521.0	521.0	-	192.00	-	256.00	-
30"	762.0	559.0	559.0	-	228.00	-	304.00	-
32"	812.8	597.0	597.0	-	249.00	-	331.00	-
34"	863.6	635.0	635.0	-	295.00	-	393.00	-
36"	914.4	673.0	673.0	-	334.00	-	441.00	-
38"	965.2	711.0	711.0	-	358.00	-	549.00	-
40"	1016.0	749.0	749.0	-	383.00	-	511.00	-
42"	1066.8	762.0	711.0	-	416.00	-	557.00	-
44"	1117.8	813.0	762.0	-	448.00	-	597.00	-
46"	1168.4	851.0	800.0	-	483.00	-	646.00	-
48"	1219.2	889.0	838.0	-	518.00	-	691.00	-

General Notes:

1) All dimensions are in mm

2) Dimension tolerance are as per ASME B16.9